

TAPER DIMENSIONS AND ELECTRODE CODING

NSRW Co., Inc. (800) 933-6779, FAX: (205) 663-3221 Authorized Distributor CMW Inc.



Standard Tapered Electrode Theoretical Dimensions	Taper Size	Standard Male Taper Cap taper Dimensions
	4RW 1MT	
	5RW 2MT	
	6RW	
	7RW 3MT	

Drawings Full Size

CMW CODING FOR STRAIGHT TAPERED ELECTRODES

Material	Nose	Attachment	Length
1 = CMW® 28	1 = Dome	1 = No. 4RW	1 = 1"
	2 = Pointed	No. 1MT	2 = 1 1/4"
3 = CMW® 3	3 = Flat		3 = 1 1/2"
5 = CMW® 100	4 = Offset	2 = No. 5RW	4 = 1 3/4"
6 = ELKONITE® 10W3	5 = 2" Sph. R	No. 2MT	5 = 2"
7 = ELKONITE® TC5	6 = 10" Sph. R.		6 = 2 1/4"
8 = ELKON® 100M	7 = Truncated	3 = No. 7RW	7 = 2 1/2"
9 = ELKON® 100W	8 = 3" Sph. R	No. 3MT	8 = 2 3/4"
	9 = 4" Sph. R		9 = 3"
	0 = Shank for Male Cap	4 = No. 6RW	12 = 3 1/4"
			14 = 3 1/2"
			16 = 3 3/4"
			18 = 4"
			20 = 4 1/4"
			22 = 4 1/2"
Note: Prefix MP = Shank for Female Cap			

RWMA CODING FOR STRAIGHT TAPERED ELECTRODES

Nose	Material	Attachment	Length in no. of 1/4"
A = Pointed	1 = RWMA CL 1 CMW® 28	4 = No. 4RW No. 1MT	04 = 1" 05 = 1 1/4" 06 = 1 1/2" 07 = 1 3/4"
B = Dome		5 = No. 5RW No. 2MT	08 = 2" 09 = 2 1/4" 10 = 2 1/2" 11 = 2 3/4"
C = Flat	2 = RWMA CL 2 CMW® 3		12 = 3" 13 = 3 1/4" 14 = 3 1/2" 15 = 3 3/4"
D = Offset	3 = RWMA CL 3 CMW® 100	6 = No. 6RW	16 = 4" 17 = 4 1/4" 18 = 4 1/2"
E = Truncated		7 = No. 7RW No. 3MT	